

ELATION® OPTI QUAD PAR™
DMX Channel Values / Functions VERSION 2 (9 DMX Channels)

Specifications are subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
1 CH	3 CH	5 CH	6 CH	8 CH	9CH		
		1	1	1	1		RED* *RED Control Disabled when fixture is in 8 or 9 CH Mode and CH 5 Color Macros are being used.
						0-255	RED (0-100%)
		2	2	2	2		GREEN* *GREEN Control Disabled when fixture is in 8 or 9 CH Mode and CH 5 Color Macros are being used.
						0-255	GREEN (0-100%)
		3	3	3	3		BLUE* *BLUE Control Disabled when fixture is in 8 or 9 CH Mode and CH 5 Color Macros are being used.
						0-256	BLUE (0-100%)
		4	4	4	4		WHITE* *WHITE Control Disabled when fixture is in 8 or 9 CH Mode and CH 5 Color Macros are being used.
						0-255	WHITE (0-100%)
							COLOR MACROS
						0	OFF
						1-4	COLOR MACRO 1
						5-8	COLOR MACRO 2
						9-12	COLOR MACRO 3
						13-16	COLOR MACRO 4
						17-20	COLOR MACRO 5
						21-24	COLOR MACRO 6
						25-28	COLOR MACRO 7
						29-32	COLOR MACRO 8
						33-36	COLOR MACRO 9
						37-40	COLOR MACRO 10
						41-44	COLOR MACRO 11
						45-48	COLOR MACRO 12
						49-52	COLOR MACRO 13
						53-56	COLOR MACRO 14
						57-60	COLOR MACRO 15
						61-64	COLOR MACRO 16
						65-68	COLOR MACRO 17
						69-72	COLOR MACRO 18
						73-76	COLOR MACRO 19
						77-80	COLOR MACRO 20
						81-84	COLOR MACRO 21
						85-88	COLOR MACRO 22
						89-92	COLOR MACRO 23
1	1			5	5	93-96	COLOR MACRO 24
						97-100	COLOR MACRO 25
						101-104	COLOR MACRO 26
						105-108	COLOR MACRO 27
						109-112	COLOR MACRO 28
						113-116	COLOR MACRO 29
						117-120	COLOR MACRO 30
						121-124	COLOR MACRO 31
						125-128	COLOR MACRO 32
						129-132	COLOR MACRO 33
						133-136	COLOR MACRO 34
						137-140	COLOR MACRO 35
						141-144	COLOR MACRO 36
						145-148	COLOR MACRO 37
						149-152	COLOR MACRO 38
						153-156	COLOR MACRO 39
						157-160	COLOR MACRO 40
						161-164	COLOR MACRO 41
						165-168	COLOR MACRO 42
						169-172	COLOR MACRO 43
						173-176	COLOR MACRO 44
						177-180	COLOR MACRO 45
						181-184	COLOR MACRO 46
						185-188	COLOR MACRO 47
						189-192	COLOR MACRO 48

ELATION | **OPTI QUAD PAR™** | **dmx traits**

ELATION® OPTI QUAD PAR™
DMX Channel Values / Functions VERSION 2 (9 DMX Channels)

Specifications are subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
1 CH	3 CH	5 CH	6 CH	8 CH	9CH		
1	1			5	5		COLOR MACROS [continued]
						193-196	COLOR MACRO 49
						197-200	COLOR MACRO 50
						201-204	COLOR MACRO 51
						205-208	COLOR MACRO 52
						209-212	COLOR MACRO 53
						213-216	COLOR MACRO 54
						217-220	COLOR MACRO 55
						221-224	COLOR MACRO 56
						225-228	COLOR MACRO 57
						229-232	COLOR MACRO 58
						233-236	COLOR MACRO 59
						237-240	COLOR MACRO 60
						241-244	COLOR MACRO 61
245-248	COLOR MACRO 62						
249-252	COLOR MACRO 63						
							COLOR MACRO 64
				6	6		STROBE / SPEED*
							*SPEED Control ONLY available when fixture is in 9 CH Mode and CH 7 DMX Value is (128-223)
						0-15	NO STROBE / OFF
						16-255	STROBE Effect SLOW to FAST
						0-255	*SPEED Control SLOW to FAST
					7		MODE
						0-127	NO Function
						128-159	Automatic COLOR Mixing
						160-191	3 COLOR Change
						192-223	7 COLOR Change
224-255	64 COLOR MACRO SOUND Active						
	2		5	7	8		DIMMER INTENSITY
						0-255	Intensity 0 to 100%
	3	5	6	8	9		DIMMING CURVE MODES
						0-20	STANDARD
						21-40	STAGE
						41-60	TV
						61-80	ARCHITECTURAL
						81-100	THEATRE
101-255	Default to Unit Setting						

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu