

Material Safety Data Sheet OSHA's Hazard Communication Standard U.S. Department of Labor

29 CFR 1910.1200

OMB No. 1218-0072

Identity #	Name 2	X- Fog Pro			
Section 1 Manufacture's Name - Address - 310 Reed Circle City - Corona State - CA	U.S. Continent	Emerç Daytir	gency Phone (Che me Phone - 1-(95 ct Person - Robert		
Date Prepared- 9/27/2007					
Section 2 - Hazardous Ingredients/Identity Information					
Hazardous Components	CAS#	OSHA PEL	ACGIH TLV	Weight% (Optional)	
None	NONE	NONE	NONE		
Note: No Hazardous Com	oonents as Listed	in 29 CFR 190	00.1000 or other p	ertinent OSHA regulations	
VOC Content- 539 g/L					
Section 3 - Physical/Chemical Cha	racteristics				
Boiling Point- >212 F Specific Gravity- 1.12					
Vapor Pressure - Not Tested Vapor Density - Not Tested			g Point - Not Teste		
Solubility In Water- 100%		⊏vapo	ration Rate - Not T	esteu	
Appearance and Odor- Green,	Bland Odor				
Section 4 - Fire and Explosion Haz	ard Data				
Flash Point- None					
LEL- Not Tested		UEL- Not Tested			
pH- 6.5-8.0		0LL			
NFPA Hazard Rating - H F		HMIS Hazard I	0	F R	
(0- Least, 4- Extreme 0 0	0 0		0	0 0	
Extinguishing Media- None Special Fire Fighting Procedures					
Special file Fighting Flocedules	NONE				
Unusual Fire and Explosion Haza	rds NONE				
Section 5 - Reactivity Data					
Stability - Stable					
Conditions to Avoid - None					
Incompatible Materials to Avoid-	Strong Oxidize	ers			
Hazardous Decomposition or Byp Hazardous Polymerization NON		CO2			
nazaruous roiyinenzalion NO					

Conditions to Avoid- None

## Section 6 - Health Hazard Data

Routes of Entry Inhalation? - Possible Skin? - Possible Ingestion? - Possible Health Hazards - Same as Signs and Symptoms of Exposures Note - All Chemicals in this Product are Found on the TSCA Inventory List. OSHA Carcinogenicity? - None; NTP? - None; IARC Monographs? - None.

#

Signs and symptons of over exposure:

Eyes - Burning Sensation

Skin- Not Expected to be a Problem

Ingestion-Nausea

Inhalation- Not Expected to be a Problem

Medical Conditions Generally Aggraved by Exposure - Same as Signs and Symptoms of Over Exposure.

Emergency and First Aid Procedures

Eyes - Flush With Water For 15 Minutes. If Irritation Persists, Call Physician.

Skin- Wash Off With Water

Ingestion- Drink Large Amounts of Water, Call Physician

Inhalation- Not Expected to be a Problem

Section 7 - Precautions For Safe Handling and Use. Steps to be taken in case material is released or spilled - Soak up with inert, absorbant material. Scoop up and place in a proper waste disposal container.

Waste Disposal Method - Dispose of in accordinance with state and local regulations. Precautions To Be Taken In Handling and Storing - Store in a cool, dry place, out of direct sunlight. Do not freeze, less than or equal to 32 F, or heat above 110 F.

Other Precautions - Keep out of reach of children. Follow directions on the container for proper use of this product.

Section 8 - Control Measures Respiratory Protection - Open all doors and windows. "If" and when there is an exposure, and it is above the TLV or PEL, a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CRF 1910.134, is required. Ventilation Local Exhaust - If Available Special - None Mechanical - If Available Other - None

Protective Gloves- None

Eye Protection- None

Other Protective Clothing or Equipment None

Work Hygenic Practices - Use common sense and care around chemicals. Never mix chemicals. Consult your supervisor for other practices. All practices depend on your specific business. Directions for use are normally found on label which will dictate engineering and control measures. Other Special Requirements

Note: USCM believes the data set forth are accurate. USCM makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion