



NETRON

OBSIDIAN
CONTROL SYSTEMS



OBSIDIAN™
CONTROL SYSTEMS

OBSIDIAN
CONTROL SYSTEMS

NETRON is a comprehensive data distribution range of rugged, reliable and easy to configure devices, offering affordable smart solutions for the professional lighting and AV markets.

NETRON devices support applications from live production and venue installations to architectural environments.

Our products are developed with the user in mind, combining tough hardware with smart software, for fast setup and solid performance.

- . Simple and efficient configuration via the on-board web interface or device OLED display
- . Instant Plug & Play through the interactive presets for recall of NETRON or user configurations
- . Advanced Cue Engine for standalone or backup operation
- . Remote Input triggers for external control
- . Device start and signal loss logic ensures your venue is never in the dark

NETRON is hardened for life on the road or the daily abuse in your venue. The scratch resistant powder coating is rated for hurricane force winds and constant exposure to the elements.

We chose this thermally fused finish for superior protection and ensures NETRON

devices looks its best for many years of service.

Precision milled aluminum chassis gives NETRON devices incredible strength while being lightweight and extremely impact resistant.

M10

INDEX

- 06 EN12
- 07 EN4
- 22 EP4
- 23 RDM 10
- 24 RDM 6XL
- 25 RDM 645



©2021 Obsidian Control Systems- all information subject to change without notice.

EP4



EN4



EN12



RDM6XL



RDM645



RDM10



EN12

The NETRON EN12 is a powerful high-density Ethernet to DMX gateway with twelve RDM compatible ports. Easy to configure with a range of integrated presets plus a wide array of advanced merge and routing features it is the ideal device for live production or installations requiring a lot of physical DMX ports. Contact closures allow for recall of presets, routings, mergers or any of the internal cues. [VISIT WEBSITE](#)

Key Features

- RDM, Artnet and sACN support
- Factory and user presets for plug and play setups
- Line Voltage or POE powered
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Customizable routing and merging options
- Remote configuration via internal webpage
- Contact closures for cue or preset recall
- Powder-coated aluminum rack mount housing

Connections

FRONT

- . (12) 5pin DMX/RDM optically isolated ports
- . Ports are bidirectional for DMX In and Output
- . Full color OLED display
- . Encoder w. Push to Select / Exit Button

BACK

- . (2) Locking RJ45 Ethernet network In
- . (10) Contact Closures (Terminal Block)
- . Locking Power In/Thru

Physical

- . Length: 482.5 mm (19 in.)
- . Width: 146 (5.7mm)
- . Height: 44 mm (1.7 in.)
- . Weight: 1.82 kg (4 lbs)

Electrical

- . 100-240 V nominal, 50/60 Hz
- . POE 802.3af



EN4

The NETRON EN4 is a powerful Ethernet to DMX gateway with four RDM compatible ports. Designed for live production and installations with a rugged housing and high-performance processing it offers flexible mounting options to cover any situation. [VISIT WEBSITE](#)

Key Features

- RDM, Artnet and sACN support
- Factory and user presets for plug and play setups
- Line Voltage or POE powered
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Remote configuration via internal web page
- Powder-coated aluminum 1/2 rack housing



NET SHELF
· Optional rack mount accessory

Connections

FRONT

- (4) 5pin DMX/RDM optically isolated ports
- Ports are bidirectional for DMX In and Output
- Full color OLED display
- Encoder w. Push to Select / Exit Button

BACK

- Locking Power In/Thru
- (2) Locking RJ45 Ethernet network connections (1x POE)

Mounting

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- Wall-mount horizontal or vertical (included)
- DIN Rail horizontal or vertical (included)
- Rack-mount option (requires NET Shelf)



Physical

- Length: 215 mm (8.5 in.)
- Width: 139 mm (5.5 in.)
- Height: 42 mm (1.65 in.)
- Weight: 1 kg (2.2 lbs)

Electrical

- 100-240 V nominal, 50/60 Hz, 10W
- POE 802.3af

EP4

The NETRON EP4 is a compact Ethernet to DMX gateway with four RDM compatible ports. It is configurable via its internal web remote and powered over Ethernet or via the USB-C connection.

[VISIT WEBSITE](#)

Key Features

- RDM, Artnet and sACN support
- Factory and user presets for plug and play setups
- POE or USB-C powered
- 99 Internal cues with fade and delay time
- Remote configuration via internal webpage
- Powder-coated aluminum housing



· Tablet not included

Connections

FRONT

- (4) 5pin DMX/RDM optically isolated ports
- Ports are bidirectional for DMX In and Output

BACK

- (2) Locking RJ45 Ethernet network connections (1x POE)
- USB-C power option (5V, 2A)

Mounting

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- Wall-mount horizontal or vertical (included)
- DIN Rail horizontal or vertical (included)

Physical

- Length: 133.5 mm (5.3 in.)
- Width: 118 mm (4.6 in.)
- Height: 42 mm (1.65 in.)
- Weight: 0.5 kg (1.1 lbs)

Electrical

- USB-C 5V
- POE 802.3af



RDM 10

The NETRON RDM 10 is a first of its kind hybrid splitter. Dual DMX input, 10 port RDM Splitter, Merger and EtherDMX Gateway are unified into the RDM10, with an advanced feature set to cover a wide variety of applications. 99 internal cues, factory and user presets plus external contact closures provide a unique combination of multiple devices to solve many required tasks in one powerful unit. [VISIT WEBSITE](#)

Key Features

- 10 assignable DMX outputs
- Integrated 2 Universe Artnet/sACN node
- Configurable DMX refresh rate
- Dual DMX Inputs for backup and signal loss options
- Remote configuration via internal webpage
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Contact closures for cue or preset recall
- Powder-coated aluminum rackmount housing

Connections

- FRONT**
- . (2) 5pin DMX Input
 - . (10) 5pin Opto-Isolated DMX Outputs
 - . Full color OLED display
 - . Encoder w. Push to Select / Exit Button
- BACK**
- . (2) 5pin DMX Input (parallel with front)
 - . (2) 5pin DMX Through
 - . (2) Locking RJ45 Ethernet Network In
 - . (10) Contact Closures (Terminal Block)
 - . Locking Power In/Thru

Physical

- . Length: 482.5 mm (19 in.)
- . Width: 146 mm (5.7 in.)
- . Height: 44 mm (1.7 in.)
- . Weight: 1.82 kg (4 lbs)

Electrical

- . 100-240 V nominal, 50/60 Hz, 10W
- . POE 802.3af



RDM 6XL

The NETRON RDM 6XL is a rugged and compact DMX/RDM Splitter. Designed for live production and installations, it features six opto-isolated 5pin XLR outputs and flexible mounting options to cover any situation.

[VISIT WEBSITE](#)

Key Features

- (6) XLR 5pin outputs
- DMX and RDM compliant
- Optically isolated ports
- Power / DMX Through connectors
- Powder-coated aluminum 1/2 rack housing



TRUSS MOUNT
Vertical or horizontal mountig with clamp

Connections

- FRONT**
- . 5pin DMX Input
 - . (6) 5pin Opto-Isolated DMX Outputs
 - . RDM Enable
- BACK**
- . 5pin DMX Input (parallel with front)
 - . 5pin DMX Through
 - . Terminate
 - . Locking Power In/Thru

Physical

- . Length: 215 mm (8.5 in.)
- . Width: 139 mm (5.5 in.)
- . Height: 42 mm (1.65 in.)
- . Weight: 1 kg (2.2 lbs)

Electrical

- . 100-240 V nominal, 50/60 Hz, 10W

Mounting

- . Standalone
- . Truss-mount (M10 or M12 mounting hole)
- . Wall-mount horizontal or vertical (included)
- . DIN Rail horizontal or vertical (included)
- . Rack-mount option (requires NET Shelf)



RDM 645

The NETRON RDM 645 is a rugged and compact DMX/RDM Splitter. Featuring six opto-isolated RJ45 DMX outputs and flexible mounting options to cover any situation.

[VISIT WEBSITE](#)

Key Features

- (6) Locking RJ45 Ethernet DMX outputs
- DMX and RDM compliant
- Optically isolated ports
- Power / DMX Through connectors
- Powder-coated aluminum 1/2 rack housing



NET SHELF
· Optional rack mount accessory

Connections

- FRONT**
- Locking RJ45 Ethernet DMX Input
 - (6) Locking RJ45 Ethernet Opto-Isolated DMX Outputs
 - RDM Enable
- BACK**
- Locking RJ45 Ethernet DMX Input (parallel with front)
 - Locking RJ45 Ethernet DMX Through
 - Terminate
 - Locking Power In/Thru

Mounting

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- Wall-mount horizontal or vertical (included)
- DIN Rail horizontal or vertical (included)
- Rack-mount option (requires NET Shelf)

Physical

- Length: 215 mm (8.5 in.)
- Width: 139 mm (5.5 in.)
- Height: 42 mm (1.65 in.)
- Weight: 1 kg (2.2 lbs)

Electrical

- 100-240 V nominal, 50/60 Hz, 10W



REFINED BY PASSION

Obsidian Control Systems combines over 25 years of experience developing professional entertainment lighting control solutions for automated and theatrical lighting fixtures.

ONYX

The lighting control software engine that powers the entire system. The ONYX platform scales from simple setup to complex touring shows with ease. Multiple hardware choices from USB wings to powerful consoles allows users to select the best surface for the budget and application. One simple platform, no simplistic feature-limited editions. ONYX is designed to grow with the user and shows, offering smart options and affordable solutions along the way. [READ MORE](#)

DYLOS

The advanced pixel composer and media engine powering ONYX. Create the most powerful FX with remarkable ease. Access hundreds of variations of any media file or effect. DYLOS gives the operator a full media engine without limitations. Fully integrated in the workflow of ONYX. DYLOS truly breaks new ground in combining a traditional lighting console with an advanced media engine in a totally integrated system. [READ MORE](#)

NETRON

OBSIDIAN™

CONTROL SYSTEMS

obsidiancontrol.com

OBSIDIAN
CONTROL SYSTEMS