

HYDRO WASH XI9

760W IP65 Moving Head Wash

The ADJ Hydro Wash X19 is an IP65 rated 760W professional moving head wash fixture with nineteen 40W RGBW (4-IN-1) LEDs.

With robust construction and IP65-ratings, the Hydro Wash X19 is designed for both indoor or outdoor use. Its durable metal casing protects it from dust, sand, moisture and liquids, making it ideal for use in all situations from dusty deserts in California to rainy fields in England. Perfect for festivals and outdoor events, as well as installation in open-air clubs and other outside entertainment spaces where wash lighting is a must. This groundbreaking fixture offer an extended operational life and reduced maintenance requirement due to its long-life LED and sealed casing design.

The Hydro Wash X19 has a wealth of features such as motorized focus (6 ~ 40-degrees), WiFLY wireless DMX, fine pan/tilt and dimming, 6 dimmer modes, LED refresh rate and gamma control settings.

Its fitted with 5-pin DMX In/Out and electrical In/Out connectors to daisy chain power. It offers a RJ45 port for software updates. All connections are IP65 rated with rubber protective covers.

The ADJ Hydro Series were awarded the 2019 PLSN Gold Star Award for "Best Range of Waterproof Fixtures."





HYDRO WASH XI9



Light Source:

• 19x Osram 40W RGBW (4-IN-1) LEDs

Features:

- IP65 outdoor rated protects fixture from dust, sand, moisture and liquid
- Motorized Zoom: 6 ~ 40-degrees
- Firmware Upgrade: Update via IP65 RJ45 port (with rubber protective cover)
- Fully pixel mappable

Contruction:

- Color display with touch buttons
- Data In/Out: 5-pin DMX IP65 (with rubber protective covers over connections)
- Power In: IP65 locking power input (with rubber protective covers over connection)
- All metal case design)

Pan/Tilt:

- Pan/Tilt: 540-degrees / 230-degrees
- 16-bit Fine Pan
- 16-bit Fine Tilt





IP65 PROTECTIVE CONNECTIONS



HYDRO WASH XI9









Control:

- WiFLY EXR Wireless DMX built-in (Up to 2,500 ft / 700M line of sight)
- Fully pixel mappable
- 3 DMX channel modes: 16, 88 & 90 channels
- Protocols: DMX-512, RDM, KlingNet and Artnet
- Control modes: DMX-512, KlingNet and Artnet
- 0-100% dimming plus 16-bit fine dimming
- 6 dimmer modes
- Strobe & pulse effects
- Gamma correction: 1.0, 2.0, 2.2, 2.4, 2.6 and 2.8
- With Wired Digital Communication Network

Electrical:

- Multi-voltage operation: 100-240V, 50/60Hz
- Maximum power draw: 990W

Dimensions & Weight:

- Dimensions (LxWxH): 15.25" x 11" x 20.75" / 384x275x524mm
- Weight: 53 lbs. / 24 kg.
- All metal case design)

Approval / Ratings:

• cETLus Approved (Control #4000358)

