

ELATION© DW PENDANT™								
DMX Channel Values / Functions (7 DMX Channels)								
Supports Software Versions: ≥ 1.03								
Features are subject to change without any prior written notice.								
DMX CHANNEL MODE							VALUE	FUNCTION
1CH	2CH	3CH	4CH	5CH	6CH	7CH		
	1	1	1	1	1	1	0	COOL WHITE Cool White (0=Black - 255=100%)
	2	2	2	2	2	2	0	WARM WHITE Warm White (0=Black - 255=100%)
1		3				3	0	COLOR TEMPERATURE OFF
							1-255	2,900K - 6,800K (1=2,900K - 255 = 6,800K)
					3	4		FLASH / STROBE
							0-31	OFF
							32-95	Variable Strobe SLOW to FAST
							96-127	Fade ON, Fade OFF SLOW to FAST
							128-159	Fade ON, Snap OFF SLOW to FAST
							160-191	Snap ON, Fade OFF SLOW to FAST
							192-223	Random Strobe SLOW to FAST
							224-255	ON
			3	3	4	5	0-255	MASTER DIMMER Intensity 0 to 100%
			4	4	5	6	0-255	MASTER DIMMER FINE (16 bit) 0 to 100%
								DIMMING CURVE MODES
							0-20	STANDARD
							21-40	STAGE
							41-60	TV
							61-80	ARCHITECTURAL
							81-100	THEATRE
				5	6	7	101-255	Default to Unit Setting

ELATION | DW PENDANT™ | dmx traits

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

DMX TRAITS CHANGE WITH SOFTWARE UPDATE VERSIONS ≥ 1.05

See highlighted items below which have been updated with this software update.

ELATION® DW PENDANT™								
DMX Channel Values / Functions (7 DMX Channels)								
Supports Software Versions: ≥ 1.05								
Features are subject to change without any prior written notice.								
DMX CHANNEL MODE							VALUE	FUNCTION
1CH	2CH	3CH	4CH	5CH	6CH	7CH		
	1	1	1	1	1	1	0	COOL WHITE Cool White (0=Black - 255=100%)
	2	2	2	2	2	2	0	WARM WHITE Warm White (0=Black - 255=100%)
1		3				3	0	COLOR TEMPERATURE OFF
							1-255	2,900K - 6,800K (1=2,900K - 255 = 6,800K)
								FLASH / STROBE
							0-31	LED OFF
							32-63	LED ON
							64-95	Strobe SLOW to FAST
							96-127	LED ON
							128-159	Pulse Strobe SLOW to FAST
							160-191	LED ON
							192-223	Random Strobe SLOW to FAST
							224-255	LED ON
			3	3	4	5	0-255	MASTER DIMMER Intensity 0 to 100%
			4	4	5	6	0-255	MASTER DIMMER FINE (16 bit) 0 to 100%
								DIMMING CURVE MODES
							0-20	STANDARD
							21-40	STAGE
							41-60	TV
							61-80	ARCHITECTURAL
							81-100	THEATRE
				5	6	7	101-255	Default to Unit Setting

ELATION | DW PENDANT™ | dmx traits

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu