

ELATION® DW CHORUS 12™

DMX Channel Values / Functions Version 1 (7 DMX Channels)

Specifications are subject to change without any prior written notice.

*Control of LED Modules depends on the Pixel Flip setting.

| MODE / CHANNEL | | | | | | | VALUE | FUNCTION |
|----------------|------|------|-------|-------|------|------|---------|---------------------------------------|
| 1 CH | 2 CH | 3 CH | 4+ CH | 5+ CH | 4 CH | 5 CH | 7 CH | |
| 1 | | | | | | | | ALL LEDs |
| | | | | | | | 0-255 | VARIABLE COLOR TEMP 2,700-6,700K |
| | 1 | 1 | 1 | 1 | | | | COOL WHITE - LED GROUP 1 + 2 |
| | | | | | | | 0-255 | 0 to 100% |
| | 2 | 2 | 2 | 2 | | | | WARM WHITE - LED GROUP 1 + 2 |
| | | | | | | | 0-255 | 0 to 100% |
| | | | | | 1 | 1 | 1 | COOL WHITE - LED GROUP 1 |
| | | | | | | | 0-255 | 0 to 100% |
| | | | | | 2 | 2 | 2 | WARM WHITE - LED GROUP 1 |
| | | | | | | | 0-255 | 0 to 100% |
| | | | | | 3 | 3 | 3 | COOL WHITE - LED GROUP 2 |
| | | | | | | | 0-255 | 0 to 100% |
| | | | | | 4 | 4 | 4 | WARM WHITE - LED GROUP 2 |
| | | | | | | | 0-255 | 0 to 100% |
| | | | | | | | | STROBE |
| | | | | | | | 0-31 | NO Function |
| | | | | | | | 32-95 | Variable Strobe Effect SLOW to FAST |
| | | | 3 | 3 | | | 96-127 | LEDs ON |
| | | | | | | | 128-159 | Pulse Effect In Sequence SLOW to FAST |
| | | | | | | | 160-191 | LEDs ON |
| | | | | | | | 192-223 | Random Strobe Effect SLOW to FAST |
| | | | | | | | 224-255 | LEDs ON |
| | | 3 | 4 | 4 | | 5 | 6 | MASTER DIMMER |
| | | | | | | | 0-255 | Intensity 0 to 100% |
| | | | | | | | | DIMMING CURVE MODES |
| | | | | | | | 0-20 | STANDARD |
| | | | | | | | 21-40 | STAGE |
| | | | | 5 | | | 41-60 | TV |
| | | | | | | | 61-80 | ARCHITECTURAL |
| | | | | | | | 81-100 | THEATRE |
| | | | | | | | 101-255 | Default to Unit Setting |

ELATION | DW CHORUS 12™ | dmx traits

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu