

ELATION® DW CHORUS 48™
DMX Channel Values / Functions Version 1 (19 DMX Channels)

Specifications are subject to change without any prior written notice.

**Control of LED Modules depends on the Pixel Flip setting.*

MODE / CHANNEL								VALUE	FUNCTION
1 CH	2 CH	3 CH	4 CH	5 CH	16 CH	17 CH	19 CH		
1									ALL LEDs
								0-255	VARIABLE COLOR TEMP 2,700-6,700K
	1	1	1	1					COOL WHITE - LED GROUP 1 - 8
								0-255	0 to 100%
	2	2	2	2					WARM WHITE - LED GROUP 1 - 8
								0-255	0 to 100%
					1	1	1		COOL WHITE - LED GROUP 1
								0-255	0 to 100%
					2	2	2		WARM WHITE - LED GROUP 1
								0-255	0 to 100%
					3	3	3		COOL WHITE - LED GROUP 2
								0-255	0 to 100%
					4	4	4		WARM WHITE - LED GROUP 2
								0-255	0 to 100%
					5	5	5		COOL WHITE - LED GROUP 3
								0-255	0 to 100%
					6	6	6		WARM WHITE - LED GROUP 3
								0-255	0 to 100%
					7	7	7		COOL WHITE - LED GROUP 4
								0-255	0 to 100%
					8	8	8		WARM WHITE - LED GROUP 4
								0-255	0 to 100%
					9	9	9		COOL WHITE - LED GROUP 5
								0-255	0 to 100%
					10	10	10		WARM WHITE - LED GROUP 5
								0-255	0 to 100%
					11	11	11		COOL WHITE - LED GROUP 6
								0-255	0 to 100%
					12	12	12		WARM WHITE - LED GROUP 6
								0-255	0 to 100%
					13	13	13		COOL WHITE - LED GROUP 7
								0-255	0 to 100%
					14	14	14		WARM WHITE - LED GROUP 7
								0-255	0 to 100%
					15	15	15		COOL WHITE - LED GROUP 8
								0-255	0 to 100%
					16	16	16		WARM WHITE - LED GROUP 8
								0-255	0 to 100%
									STROBE
								0-31	NO Function
								32-95	Variable Strobe Effect SLOW to FAST
			3	3			17	96-127	LEDs ON
								128-159	Pulse Effect In Sequence SLOW to FAST
								160-191	LEDs ON
								192-223	Random Strobe Effect SLOW to FAST
								224-255	LEDs ON
		3	4	4		17	18		MASTER DIMMER
								0-255	Intensity 0 to 100%

ELATION | **DW CHORUS 48™** | **dmx traits**

ELATION® DW CHORUS 48™

DMX Channel Values / Functions Version 1 (19 DMX Channels)

Specifications are subject to change without any prior written notice.

*Control of LED Modules depends on the Pixel Flip setting.

MODE / CHANNEL								VALUE	FUNCTION
1 CH	2 CH	3 CH	4 CH	5 CH	16 CH	17 CH	19 CH		
				5			19		DIMMING CURVE MODES
								0-20	STANDARD
								21-40	STAGE
								41-60	TV
								61-80	ARCHITECTURAL
								81-100	THEATRE
								101-255	Default to Unit Setting

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu